

TerraTec

128 i PCI

PCI Sound Card



TerraTec 128i PCI - Big Sound... Small Price

Reap the benefit of advancing technology with the TerraTec 128i PCI sound card. The sound-chip technology delivers a level of audio quality previously only available from high-end sound cards.

Full compatibility with Windows 95/98/ME/NT4/2000 and Plug & Play means installing the TerraTec 128i PCI is child's play itself. Microsoft DirectX™ compatibility ensures perfect sound from all the latest games as well as legacy SoundBlaster™ Pro compatibility for all those old favourites.

For flawless MIDI playback, the TerraTec 128i PCI comes with a wavetable synthesizer with a 1Mbyte and 3 MB General MIDI soundset, available to choose from.

Internal connectors are provided for audio inputs from CD-ROM and Aux for the ReceiverSystem TerraTV+ or a similar product. External connections are provided for a mono microphone, stereo line input and stereo line output for active speakers as well as a standard gameport connector for joysticks and MIDI.

Together with the bundled AudioRack software, the TerraTec 128i PCI will form the heart of your PC based home entertainment system.

If all of this were not enough, we have included IBM VoiceType Control, an incredible piece of software that allows you to control your computer through voice commands.

Key Features.

PCI Plug & Play


Real-Mode DOS SoundBlaster/-PRO compatible

Integrated Software Wavetable

3D Sound (VSpace)

Enhanced Full Duplex

Driver for MS-DOS 7.0,



Technische Details:

Compatibility.

- Microsoft DirectSound
- Microsoft DirectSound 3D
- General MIDI
- MPU-401 compatible
- SoundBlaster / Pro
- OPL3 compatible hardware FM synthesis

Digital Audio.

- VSpace™ 3D Effect
- 8/16 Bit Record & Playback at up to 48kHz in mono / stereo
- Enhanced Full Duplex
- Record & Playback of all audio sources

Software Wavetable.*

- 32 voices, simultaneous
- 1 MB Sample-Set
- 3MB Sample-Set
- GM compatible

Audio Mixer.

- Individual volume control of all audio sources

MIDI/Joystick Interface.

- DirectInput compatible
- MPU-401 (UART Modus) compatible
- SoundBlaster compatible MIDI Interface
- Standard Dual gameport (via Y-Adapter)

External connectors.

- Line Out (3,5 mm jack)
- Line In (3,5 mm jack)
- Mic In (3,5 mm jack)
- MIDI/Joystick Interface (IBM 15pin Sub-D)

Onboard connectors.

- IDE / Sony CD-Audio connectors
- AUX In, Stereo

Driver.

- Windows 95/98/ME/2000 (MS-DOS 7.0)
- Windows NT 4.0

Software.

- ESS AudioRack
- ESS Software Wavetable
- IBM VoiceType Control

System Requirements.

- One free PCI 2.1 compliant PCI Slot
- P166, P200 MMX recommended
- 16MB, 32MB recommended
- CD-ROM drive for "Driver & Software CD"
- 10 MB free disk space
- Speakers or headphones
- Windows 95, Windows 98 with DirectX 5 or higher, or Windows NT 4.0 with ServicePack 3 or higher

Package contents.

- TerraTec 128iPCI sound card
- Driver & Software CD
- Quick start guide

Art.No.: 1360

EAN-Code: 4017273613604

Warranty: 24 month

* Only available under Windows 95 & Windows 98